



(561) 243-7200 Fax: (561) 243-7221



CHECKLIST FOR COMPOSITE SHINGLES AND BUILT UP ROOF SYSTEMS

Permit Number _____

THE FOLLOWING SPECIFIES COMPOSITE SHINGLE INSTALLATION METHODS CONFORMING TO THE STANDARD BUILDING CODE, CHAPTER 15, AND TO THE BUILDING CODE ADVISORY BOARD OF PALM BEACH COUNTY AMENDMENTS:

I. Scope of Work: New Roof _____ II. Roof Slope: _____:12
Re-Roof _____
(Existing sheathing to be re-nailed 4" o/c edges and 6" o/c in field)
(Minimum slope for shingle 2:12)

III. Underlayment System: Per Standard building Code _____ Chap. 15, 1997 Standard Building Code with P. B. Cty Amendments
Per Product Approval _____
Per NTRMA Specification _____ (if selected, provide specs at inspection)

IV. Manufacturer of Shingle: (check off and provide type)

| | |
|-------------------|-----------------------|
| Atlas _____ | Inko _____ |
| Celexox _____ | Intec Permaglas _____ |
| Certainteed _____ | Malarky _____ |
| Elk _____ | GAF _____ |
| Owens _____ | Tamko _____ |
| GS _____ | U.S. Intec _____ |

V. Underlayment Attachment Method: Standard building Code, Ch. 15 for slopes

_____ 2:12 up to 4:12 – two layers of type 15 saturated, non-perforated felt applied in the following manner:
Apply a 19" strip of 15 asphalt saturated shingle underlayment felt parallel with and starting at the eaves, fastened sufficiently to hold in place. Starting at the eaves, apply 36" (94mm) wide sheets of underlayment overlapping successive sheets 19" and fastened sufficiently to hold in place. As an alternative to saturated felt, a self-adhering polymer modified bituminous sheet complying with ASTM D 1970 may be applied according to manufacturer's recommendation.

_____ 4:12 pitch to 20:12 pitch. Underlayment shall be type 15 asphalt saturated, non-perforated felt applied shingle fashion, parallel to and starting from the eave and lapped 2" (51mm) fastened only as necessary to hold in place. As an alternative to two layers of cemented saturated felt, a self-adhering polymer modified bituminous sheet complying with ASTM D 1970 may be applied according to the manufacturer's instruction.

_____ Per product approval (provide specifications to inspector in field).

****OWNER BUILDER CAN ONLY PULL A PERMIT FOR COMPOSITE SHINGLES**